



BATTERY(LV)

ABL02-05L65

ABL02-16L65



Safe & Reliable

» Low-voltage design, free from high-voltage electric shock hazards, shock-proof



Economical & Cost-Saving

» Adopts grade A lithium iron phosphate cells with cycle life exceeding 6000 times, guaranteeing over 10 years of regular service.



User-Friendly

- » Strong adaptability: Resistant to high temperature and extreme cold
- » Easy installation: Wall-mounted or floor-standing available, supports flexible multi-unit parallel connection
- » High altitude adaptability: Air circulation inside and outside battery pack, no pressure difference



Smart

» High compatibility: Compatible with mainstream low-voltage inverters

AUX GROUP

Established in 1986, AUX Group is an enterprise which covers 5 industries. It ranked China's top 500 enterprises for consecutive years, 40000+ employees keep AUX fast development for recent years.

40

Years

History

\$12

Billion

Revenue in 2025

5

Business Industries

\$11.2

Billion

Assets

500

China's Top

40000+

Employees

AUXSOL

Advance Unlimited X-tra Green Power

Ningbo AUX Solar Import & Export Co., Ltd.

No. 518, Xinmei Road, Yinzhou District, Ningbo City, Zhejiang Province, China



✉ info@auxsol.com

🌐 www.auxsol.com

☎ +86 0574-8765 2201

	ABL02-05L65	ABL02-16L65
PERFORMANCE PARAMETERS		
Cell Type	LiFePO4	
Cell Specification(Ah)	100	314
Nominal Voltage(V)	51.2	
Operating VoltageV)	43.2~58.4	
NominalEnergy(kWh)	5.12	16.07
UsableEnergy(kWh)[1]	4.6	14.46
Charge/Discharge Current(A) Recommend	100	157
Max. charge/Discharge Current(A)	100	157
PERFORMANCE PARAMETERS		
Weight(kg)[2]	52.5	120
Dimension(W*H*D ±1mm)	454*584*140	480*822*235
Parallel Quantities	Max.15 pcs in Paralle	
Life Cycle(25 C ±2 C ,90%DOD,0.5C,70%EOL)	≥6000	≥8000
Warranty	5 Years	
Operating Temperature	Charge: 0~55 C , Discharge: -20~60 C	
Storage Temperature	-20~45 C ≤1 month ; -20~35 C ≤6 month	
Relative Humidity	5%~95%(Non-condensing)	
Cooling Method	Natural Cooling	
Installation Method	Wall-mounted	Floor-standing
Installation Environment	Indoor/Outdoor	
Ingress Protection Rating[3]	IP65	
Maximum Operating Altitude[4]	≤2,000m	
Protection Strategy	Overvoltage Protection, Overcurrent Protection, Short Circuit Protection, Overtemperature Protection, Undervoltage Protection, Low-temperature Protection	
COMMUNICATION		
Display	SOC, Faults, and Operating Status	
Communication Protocol	RS485/CAN	
COMMUNICATION		
Certification	CE,UN38.3	

[1].DC Usable Energy,test conditions:90% DOD,0.5C charge & discharge at 25°C.
 [2].The weight is subject to the actual product and may have a tolerance of ±3%.
 [3].IP65 is optionally available.
 [4].Output power may be affected by altitude.