

SINGLE PHASE ON-GRID INVERTER

ASN-9SL

ASN-10SL



KEY FEATURES



High Efficiency

- » Max. MPPT current 32A, suitable for high-current/double-sided components
- » 40V low start-up voltage enables early startup and more energy generation



Smart

- » Ultra-wide grid voltage design with automatic voltage regulation technology ensures uninterrupted operation even under unstable grid conditions
- » Supports 24-hour load uninterrupted power monitoring (Optional)



User-Friendly

- » Support RS485, WiFi, 4G, LAN, Suspec different communication methods
- » Quick sweep access to AUXSOL Cloud, support remote upgrade and setup



Safe & Reliable

- » Supports I-V curve scanning, accurately identifying string anomalies
- » Intelligent AFCI reduces fire risk (Optional)



Economical & Cost-Saving

- » Compact and lightweight design for easy installation and maintenance
- » Supports high power component access, low system installation and cable costs

AUX GROUP

Established in 1986, AUX Group is an enterprise which covers 5 industries. It ranked China's top 500 enterprises for consecutive years, 40000+ employees keep AUX fast development for recent years.

40 Years History	\$11.8 Billion Revenue in 2025	5 Business Industries
\$9.6 Billion Assets	500 China's Top	40000+ Employees

AUXSOL

WIN A GREEN FUTURE TOGETHER

Ningbo AUX Solar Import & Export Co., Ltd.

No. 518, Xinmei Road, Yinzhou District, Ningbo City, zhejiang Province, China



✉ info@auxsol.com
 🌐 www.auxsol.com
 ☎ +86 0574-8765 2201

	ASN-9SL	ASN-10SL
PV INPUT		
Max. PV input power	18kW	20kW
Max. PV input voltage	600V	
Rated PV input voltage	380V	
Start-up voltage	40V	
MPPT voltage range	40-550V	
Max. PV input current	32A/16A	
Max. short circuit current	40A/20A	
MPPT number/Max. input strings number	2/3	
AC OUTPUT		
Rated output power	9kW	10kW
Max. apparent output power	9kVA	10kVA
Rated output current	40.9A	45.5A
Max. output current	40.9A	45.5A
Rated output voltage	220V/230V/240V, L/N/PE	
Output voltage range	160~300V	
Rated output frequency/frequency range	50Hz/60Hz (±5Hz)	
Power factor	>0.99 (0.8 leading ... 0.8 lagging)	
THDi	<3%	
EFFICIENCY		
MPPT efficiency	99.80%	
Max. efficiency	98.10%	
EU efficiency	97.60%	
PROTECTION		
Integrated DC switch	Yes	
DC reverse-polarity protection	Yes	
Insulation impedance detection	Yes	
Residual leakage current detection	Yes	
Ground fault monitoring	Yes	
Short circuit protection	Yes	
Anti-islanding protection	Yes	
DC/AC surge protection	DC:Type II;AC:Type II	
DC arc-fault circuit protection	Optional	
I/V curve scanning	Yes	
GENERAL		
Operating temperature range	-30...+60C	
Max. operation altitude	4000m (Derating above 3000m)	
Relative humidity	0-100%	
Cooling concept	Natural Cooling	
Ingress protection	IP66	
Topology	Transformerless	
Night self consumption	<1W	
Dimensions (W*H*D)	400*383*177mm	
Weight	16.1kg	
COMMUNICATION		
Display	LED+Bluetooth+APP (Optional:LCD)	
Communication	RS485,Optional:WIFI,4G,LAN	
CERTIFICATION		
Grid standards	EN 50549-1,IEC 61727/62116,IEC 61683,UNE 217001,UNE 217002,NTS-631,PEA,G98	
Safety/EMC	IEC/EN 62109-1/2,EN IEC61000-6-1/2/3/4,EN IEC 61000-3-11/12	