

THREE PHASE ON-GRID INVERTER

ASN-(30-40)TL-LV-G2



KEY FEATURES



High Efficiency

- » Single MPPT supports a Max. current of 48A, single string supports a Max. current of 20A, compatible with 210 large modules
- » 180V low start-up voltage enables early startup and more energy generation



Smart

- » Ultra-wide grid voltage design with automatic voltage regulation technology ensures uninterrupted operation even under unstable grid conditions
- » PID repair function to enhance system power generation (Optional)



User-Friendly

- » Support RS485, WiFi, 4G, LAN, Suspec different communication methods
- » Quick sweep access to AUXSOL Cloud, support remote upgrade and setup



Safe & Reliable

- » Supports I-V curve scanning, accurately identifying string anomalies
- » Intelligent AFCI reduces fire risk (Optional)
- » Pure film capacitors with a 25-year design lifespan



Economical & Cost-Saving

- » Intelligent string monitoring, rapid identification of faulty strings, reducing safety risks (Optional)
- » 4-way MPPT design to accommodate multi-orientation roofs

AUX GROUP

Established in 1986, AUX Group is an enterprise which covers 5 industries. It ranked China's top 500 enterprises for consecutive years, 40000+ employees keep AUX fast development for recent years.

<p>40 Years</p> <p>History</p>	<p>\$11.8 Billion</p> <p>Revenue in 2025</p>	<p>5</p> <p>Business Industries</p>
<p>\$9.6 Billion</p> <p>Assets</p>	<p>500</p> <p>China's Top</p>	<p>40000+</p> <p>Employees</p>

AUXSOL

WIN A GREEN FUTURE TOGETHER

Ningbo AUX Solar Import & Export Co., Ltd.

No. 518, Xinmei Road, Yinzhou District, Ningbo City, Zhejiang Province, China



✉ info@auxsol.com
 🌐 www.auxsol.com
 ☎ +86 0574-8765 2201

	ASN-30TL-LV-G2	ASN-40TL-LV-G2
PV INPUT		
Max. PV input power	45kW	60kW
Max. PV input voltage	800V	
Rated PV input voltage	360V	
Start-up voltage	180V	
MPPT voltage range	150-800V	
Max. PV input current	48/48/48/48A	
Max. short circuit current	60/60/60/60A	
MPPT number/Max. input strings number	4/12	
AC OUTPUT		
Rated output power	30kW	40kW
Max. apparent output power	33kVA	44kVA
Rated output current	78.7A	105A
Max. output current	86.6A	115.5A
Rated output voltage	127/220V,3L/N/PE	
Output voltage range	92-173(Phase voltage),160-300V(Line voltage)	
Rated output frequency/ frequency range	50/60Hz(±5Hz)	
Power factor	>0.99 (0.8 leading ... 0.8 lagging)	
THDi	<3%	
EFFICIENCY		
MPPT efficiency	99.80%	
Max. efficiency	98.60%	
EU efficiency	98.00%	
PROTECTION		
Integrated DC switch	Yes	
DC reverse-polarity protection	Yes	
String monitoring	Optional	
Insulation impedance detection	Yes	
Residual leakage current detection	Yes	
Ground fault monitoring	Yes	
Short circuit protection	Yes	
Anti-islanding protection	Yes	
DC/AC surge protection	DC:Type II;AC:Type II	
PID recovery	Optional	
DC arc-fault circuit protection	Yes	
I/V curve scanning	Yes	
GENERAL		
Operating temperature range	-30...+60C	
Max. operation altitude	4000m (Derating above 3000m)	
Relative humidity	0-100%	
Cooling concept	Smart Fan Cooling	
Ingress protection	IP66	
Topology	Transformerless	
Night self consumption	<1W	
Dimensions (W*H*D)	735*530*285mm	
Weight	58.8kg	
COMMUNICATION		
Display	LED+Bluetooth+APP (Optional:LCD)	
Communication	RS485,Optional:WIFI,4G,LAN	
CERTIFICATION		
Grid standards	EN50549-1,INMETRO 140,INMETRO 515	
Safety/EMC	IEC/EN 62109-1/2,EN IEC61000-6-2/4,EN IEC 61000-3-11/12	